



ON-OFF FLOAT VALVE WITH PRESSURE SUSTAINING FEATURE

03/06

970 Series

—Model— **972-09-20**
672-09-20

Specifications

The On-Off Float Control Valve with Pressure Sustaining Feature shall be a pilot operated diaphragm valve designed to open fully or close drip-tight as commanded by the Float Control Pilot. The Float Pilot may be either valve or remote mounted. The valve shall close drip tight when water level reaches the adjustable high-level setpoint, and open when water level is below the adjustable low-level setpoint, allowing a calculated “draw-down” of water level to increase tank circulation. The valve shall also throttle to sustain a minimum upstream pressure during tank filling operations.

The main valve shall be a hydraulically operated, single diaphragm actuated, globe or angle pattern valve. Y-pattern valves shall not be permitted. The valve shall contain a disc and diaphragm assembly that forms a sealed chamber below the valve cover, separating operating pressure from line pressure. The diaphragm shall be constructed of nylon reinforced Buna-N, and shall not seal directly against the valve seat and shall be fully supported by the valve body and cover. Rolling diaphragm construction will not be allowed and there shall be no pistons operating the main valve or any pilot controls.

The main valve body, cover, flanges, and all internal components shall be fabricated 304L Stainless Steel. The main valve trim and throttling components (cover bearing, valve seat and disc guide) shall be Stainless Steel.

The disc and diaphragm assembly shall contain a Buna-N synthetic rubber disc with a rectangular cross-section that is securely retained on 3-1/2 sides by a disc retainer and disc guide. Diaphragm assemblies utilizing bolts or cap screws for component retention will not be permitted.

The exposed portion of the seat disc shall contact the valve seat and seal drip-tight. The disc and diaphragm assembly must be guided by two separate bearings, one installed in the valve cover and one concentrically located within the valve seat, to avoid deflection and assure positive disc-to-seat contact. Center guided valves will not be permitted. All necessary repairs shall be made from the top of the valve while the body remains in line.

The pilot control system shall contain an On-Off Float Pilot, 3-Way Accelerator Pilot with integral orifice, Pressure Sustaining Pilot, separate Adjustable Opening and Closing Speed Controls, (2) 12” Float Rods, Float Ball, an external Y-Strainer and Isolation Ball Valves on all body connections. The pilot control system shall utilize stainless steel tubing and fittings, and all pilot control system components including valve accessories shall be stainless steel. The adjustment range of the pressure sustaining pilot shall be 20-200 psi.

The valve shall be AMES Model 972GS-09-20 / 672GS-09-20 (Globe) or 972AS-09-20 / 672AS-09-20 (Angle) On-Off Float Control Valve with Pressure Sustaining Feature.