

For Point-of-Use Water Applications

Job Name _____

Contractor _____

Job Location _____

Approval _____

Engineer _____

Contractor's P.O. No. _____

Approval _____

Representative _____

10 Series Quick-Connect Valves

Sea Tech Quick-Connect Valves are designed and manufactured for many years of trouble free service. Produced of off white polypropylene, a high performance thermoplastic material, the Sea Tech Quick-Connect design allows for quick and easy connections without the use of installation tools.

Specifications

Connection shall be made using Sea Tech 10 Series Quick-Connect fitting with Integral Collet and O-Ring Guide. Fitting shall be able to fully rotate under pressure and allow easy disconnect and reuse without the use of disconnection tools. Fitting must not disassemble to disconnect.

Approvals

NSF-61

Ratings

150psi @ 70°F (10 bar @ 20°C)

60psi @ 140°F (4 bar @ 60°C) Min. 33°F (1°C)

Example

1039-04

10 = Series 10

39 = Type 39 Union Stop Valve

04 = 1/4" OD

Caution: The polypropylene material used in the Quick-Connect fittings can be compromised by exposure to volatile organic compounds (VOC's) and caustic chemicals. Therefore, **DO NOT** expose this product to any such chemical or foreign substance, which would include exposure to the following products: **Pipe Dopes (thread sealants)**, bug sprays, lubricants, cleaners, paints, bleaches, acids, solder fluxes, plastic piping primers and cements, oxidizing agents, alkaline solutions, thinners, fuels, oil based caulks, hydrocarbons, spray foam or foaming agents (insulation).



1039



1053




1062

Sea Tech product specifications in U.S. customary units and metric are approximate and are provided for reference only. For precise measurements, please contact Sea Tech Technical Service. Sea Tech reserves the right to change or modify product design, construction, specifications, or materials without prior notice and without incurring any obligation to make such changes and modifications on Sea Tech products previously or subsequently sold.

Dimensions – Weights approx. (tolerance +/- 1/8")


Type 39 Union Stop Valve

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM HEIGHT		ITEM WEIGHT	
		A		B		lbs.	kg.
		<i>in.</i>	<i>mm</i>	<i>in.</i>	<i>mm</i>		
1039-04	1/4" OD	2 1/2	63	1 9/16	39	0.70	19.96
1039-06	3/8" OD	2 15/16	74	1 9/16	39	0.83	23.59




Type 53 Female Angle Valve

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM HEIGHT		ITEM WEIGHT	
		A		B		lbs.	kg.
		<i>in.</i>	<i>mm</i>	<i>in.</i>	<i>mm</i>		
1053-0404	1/4" OD x 1/4" NPTF	2 9/16	64	2 1/16	52	0.83	23.59
1053-0604	3/8" OD x 1/4" NPTF	2 5/8	65	2 1/16	52	0.90	25.51



Type 62 Male Stop Valve

MODEL	SIZE & CONNECTION	ITEM LENGTH		ITEM HEIGHT		ITEM WEIGHT	
		A		B		lbs.	kg.
		<i>in.</i>	<i>mm</i>	<i>in.</i>	<i>mm</i>		
1062-04	1/4" OD x 1/4" NPTF	2 11/16	68	1 9/16	39	0.72	20.41
1062-06	3/8" OD x 3/8" NPTF	3	75	1 9/16	39	0.83	23.59



A Subsidiary of Watts Water Technologies, Inc.



USA: 211 Racine Drive, Suite 201, Wilmington, NC 28403; www.seatechinc.com
Tel: 1-888-500-0056 • Fax: 1-888-500-0057