



BAEU.EX3872 Backflow Special Check Valve Devices

[Page Bottom](#)

Backflow Special Check Valve Devices

[See General Information for Backflow Special Check Valve Devices](#)**AMES CO INC**

1485 TANFORAN AVE
WOODLAND, CA 95776 USA

EX3872

Backflow special check valves for a max. working pressure of 175 psi in the following models, types and sizes:

Model	Type	Size In.	Installation Orientation
200B	DC	3/4, 1, 1-1/4, 1-1/2, 2	H, V
2000B	DC	3/4,1-1/4,1-1/2	H, V
2000B	DC	1,2	H, V
2000CIV	DC	4,6,8,10	H
2000DC	DC	10	H
2000DCA	DC	8	H
2000SE	DC	2-1/2,6,8	H, V
2000SS	DC	2-1/2,3,4,6,8,10,12	H, V
2000SSF	DC	2-1/2, 3, 4	H, V
2000B-FP	DC	3/4, 1, 1-1/4, 1-1/2, 2	H, V
2001SS	DC	3,4,6,8	H, V
2001SSN	DC	3,4,6,8	H
2001SSZ	DC	3,4,6,8	H
3001SS	DCD	3,4,6,8	H, V
3001SSN	DCD	3,4,6,8	H
3001SSZ	DCD	3,4,6,8	H
3000B	DCD	2,2-1/2	H, V
3000CIV	DCD	4,6,8,10	H
3000DCDC	DCD	10	H
3000SE	DCD	2-1/2,6,8	H, V
3000SS	DCD	2-1/2,3,4,6,8,10,12	H, V
3000SSF	DCD	2-1/2, 3, 4	H, V
3000B-FP	DCD	2	H
4000B	RP	3/4, 1-1/4, 1-1/2, 2	H, V
4000B	RP	1	H, V
400B	RP	3/4, 1, 1-1/4, 1-1/2, 2	H

4000CIV	RP	2-1/2, 3, 4, 6, 8, 10	H
4000RP	RP	6,8,10	H
4000SS	RP	2-1/2, 3,4,6,8,10	HV
4000B-FP	RP	3/4, 1, 1-1/4, 1-1/2, 2	H, V
4001SS	RP	3,4,6	H
4001SSN	RP	3,4,6	H
4001SSZ	RP	3,4,6	H
5000	RPD	4,6,8,10	H
5000CIV	RPD	2-1/2, 3, 4, 6, 8, 10	H
5000SS	RPD	2-1/2,3,4,6, 8,10	HV
5001SS	RPD	3,4,6	H
5001SSN	RPD	3,4,6	H
5001SSZ	RPD	3,4,6	H
Colt 200	DC	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
		8	H,V
		10	H,V
Colt 200N	DC	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 200	DC	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
		8	H,V
		10	H,V
Maxim 200N	DC	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Colt 200A	DC	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V

Colt 200NA	DC	2-1/2	H
		3	H
		4	H
		6	H
Maxim 200A	DC	2-1/2	H,V
		3	H,V
		4	H,V
Maxim 200NA	DC	2-1/2	H
		3	H
		4	H
Colt 300	DCDA	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
		8	H,V
		10	H,V
Colt 300N	DCDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 300	DCDA	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
		8	H,V
		10	H,V
Maxim 300N	DCDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Colt 300A	DCDA	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
Colt 300NA	DCDA	2-1/2	H
		3	H
		4	H

		6	H
Maxim 300A	DCDA	2-1/2	H,V
		3	H,V
		4	H,V
Maxim 300NA	DCDA	2-1/2	H
		3	H
		4	H
Colt 400	RP	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Colt 400N	RP	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Colt 400Z	RP	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 400	RP	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 400N	RP	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 400Z	RP	2-1/2	H
		3	H
		4	H
		6	H

		8	H
		10	H
Colt 500	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Colt 500N	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Colt 500Z	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 500	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 500N	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 500Z	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H

Last Updated on 2010-10-19

[Questions?](#)

[Print this page](#)

[Notice of Disclaimer](#)

[Page Top](#)

Copyright © 2010 Underwriters Laboratories Inc.®

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Listed and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Designs and/or Listings (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from Underwriters Laboratories Inc." must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "Copyright © 2010 Underwriters Laboratories Inc.®"

An independent organization working for a safer world with integrity, precision and knowledge.

