

RECEIVED SEP 10 2002

Northbrook, Illinois • (847) 272-8800
Melville, New York • (631) 271-6200
Santa Clara, California • (408) 985-2400
Research Triangle Park,
North Carolina • (919) 549-1400
Camas, Washington • (360) 817-5500



AMES CO INC
MR J KLOPPER
1485 TANFORAN AVE
WOODLAND CA 95776

RE: Project Number(s) - 01NK49810

Your most recent Certification is shown below. You may also view this information, or a portion of this information (depending on the product category), on UL's Online Certifications Directory at www.ul.com/database. Please review the text and contact the Conformity Assessment Services staff member who handled your project if revisions are required. For instructions on placing an order for this information in a 3 x 5-inch format, you may refer to the enclosed order form for UL Card Service.

BAEU7 August 20, 2002
Backflow Special Check Valve Devices Certified for Canada

AMES CO INC
1485 TANFORAN AVE, WOODLAND CA 95776

EX3872

Backflow special check valves for a max. working pressure of 175 psi in the following models, types and sizes:

Model	Type	Size In.	Installation Orientation
Colt 200	DC	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
		8	H,V
		10	H,V
Colt 200N	DC	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 200	DC	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
		8	H,V
		10	H,V
Maxim 200N	DC	2-1/2	H
		3	H
		4	H
		6	H

Model	Type	Size In.	Installation Orientation
Colt 200A	DC	8	H
		10	H
		2-1/2	H,V
		3	H,V
		4	H,V
Colt 200NA	DC	6	H,V
		2-1/2	H
		3	H
		4	H
		6	H
Maxim 200A	DC	2-1/2	H,V
		3	H,V
		4	H,V
Maxim 200NA	DC	2-1/2	H
		3	H
		4	H
Colt 300	DCDA	2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
		8	H,V
		10	H,V
Colt 300N	DCDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
Maxim 300	DCDA	10	H
		2-1/2	H,V
		3	H,V
		4	H,V
		6	H,V
Maxim 300N	DCDA	8	H,V
		10	H,V
		2-1/2	H
		3	H
		4	H
Colt 300A	DCDA	6	H
		8	H
		10	H
		2-1/2	H,V
		3	H,V
Colt 300NA	DCDA	4	H,V
		6	H,V
		2-1/2	H
		3	H
Maxim 300A	DCDA	4	H
		6	H
		2-1/2	H,V
		3	H,V
Maxim 300NA	DCDA	4	H,V
		2-1/2	H
		3	H

Model	Type	Size In.	Installation Orientation
Colt 400	RP	4	H
		2-1/2	H
		3	H
		4	H
		6	H
Colt 400N	RP	8	H
		10	H
		2-1/2	H
		3	H
		4	H
Colt 400Z	RP	6	H
		8	H
		10	H
		2-1/2	V
		3	V
Maxim 400	RP	4	V
		6	V
		8	V
		10	V
		2-1/2	H
Maxim 400N	RP	3	H
		4	H
		6	H
		8	H
		10	H
Maxim 400Z	RP	2-1/2	H
		3	H
		4	H
		6	H
		8	H
Colt 500	RPDA	10	H
		2-1/2	V
		3	V
		4	V
		6	V
Colt 500N	RPDA	8	V
		10	V
		2-1/2	H
		3	H
		4	H
Colt 500Z	RPDA	6	H
		8	H
		10	H
		2-1/2	V
		3	V
		4	V
		6	V
		8	V
		10	V
			V

Model	Type	Size In.	Installation Orientation
Maxim 500	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 500N	RPDA	2-1/2	H
		3	H
		4	H
		6	H
		8	H
		10	H
Maxim 500Z	RPDA	2-1/2	V
		3	V
		4	V
		6	V
		8	V
		10	V

These devices have been evaluated for friction loss, strength of body, seat leakage and elastomeric seal characteristics only.

LOOK FOR CLASSIFICATION MARK ON PRODUCT